

Logo 1	Logo 2	1/2
Site address		
<b>PART LIST</b>		
Document number:		Phase

Position	Profile	Material	Qty:	Length [mm]	Weight [kg]	Tot. weight [kg]	P. Area [m2]	Remarks
P-2088	BL6*160	S235JR	1	2010	15,15	15,15	0,67	
P-2090	BL6*160	S235JR	1	4289	32,33	32,33	1,43	
P-2091	BL6*160	S235JR	1	4058	30,59	30,59	1,35	
P-2092	BL6*160	S235JR	1	4142	31,22	31,22	1,38	
P-2093	BL6*160	S235JR	1	4142	31,22	31,22	1,38	
P-2094	BL6*160	S235JR	1	3966	29,89	29,89	1,32	
P-2095	<b>BL6*150</b>	S235JR	1	3973	29,94	29,94	1,32	
P-2097	<b>BL6*110</b>	S235JR	1	983	7,41	7,41	0,33	
P-2098	BL6*160	S235JR	1	1429	10,77	10,77	0,48	
P-2099	<b>BL6*200</b>	S235JR	1	1374	10,36	10,36	0,46	
P-2100	BL6*160	S235JR	1	1384	10,43	10,43	0,46	
P-2101	BL6*160	S235JR	1	1395	10,52	10,52	0,47	
P-2105	BL6*160	S235JR	1	1937	14,60	14,60	0,65	
P-2106	BL6*160	S235JR	1	508	3,83	3,83	0,17	
P-2107	BL6*160	S235JR	5	2022	15,24	76,21	0,67	
P-2108	BL6*160	S235JR	4	3212	24,21	96,84	4,27	
P-2109	BL6*160	S235JR	1	2000	15,40	15,40	0,50	
P-2110	BL6*160	S235JR	5	3067	23,12	115,58	5,10	
P-2111	BL6*160	S235JR	1	1986	14,97	14,97	0,66	
P-2112	BL6*160	S235JR	5	3600	30,00	150,00	1,15	
P-2113	BL6*160	S235JR	6	2190	31,00	186,00	0,73	
P-2114	BL6*160	S235JR	7	2195	32,00	224,00	0,73	
P-2115	BL6*160	S235JR	1	4149	31,27	31,27	1,38	
P-2116	BL6*160	S235JR	1	3693	27,77	27,77	1,23	
P-2117	BL6*160	S235JR	1	4149	31,27	31,27	1,38	
P-2118	BL6*160	S235JR	1	2813	21,20	21,20	0,94	
P-2119	BL6*160	S235JR	1	2184	16,46	16,46	0,73	
P-2120	BL6*160	S235JR	1	2813	21,20	21,20	0,94	
P-2121	BL6*160	S235JR	1	2184	16,46	16,46	0,73	
P-2122	BL6*150	S235JR	4	2439	17,24	68,95	3,05	
P-2123	BL6*160	S235JR	1	2725	19,79	19,79	0,87	
P-2124	BL6*160	S235JR	1	2104	16,46	16,46	0,73	
P-2126	BL6*160	S235JR	1	500	2,61	2,61	0,12	
P-2128	BL6*160	S235JR	1	1046	7,83	7,83	0,35	
P-2131	BL6*160	S235JR	1	3202	24,13	24,13	1,07	
P-2132	BL6*160	S235JR	1	275	2,07	2,07	0,09	
P-2156	BL6*160	<b>S355J2</b>	1	489	3,69	3,69	0,16	
P-2165	BL6*160	<b>S355J2</b>	2	450	3,40	6,80	0,30	
P-2166	BL6*160	<b>S355J2</b>	1	291	2,20	2,20	0,10	
P-2167	BL6*160	S235JR	1	351	2,59	2,59	0,12	
P-2258	BL6*160	S235JR	1	2184	16,46	16,46	0,73	
P-2259	BL100*6	S235JR	8	150	0,71	5,65	0,26	
P-2266	BL10*70	S235JR	1	150	0,82	0,82	0,03	
P-20200	CHS48.3*3.2	S235JRH	2	1121	3,99	7,98	0,34	
P-20201	CHS48.3*3.2	S235JRH	2	80	0,28	0,57	0,02	
P-20202	CHS48.3*3.2	S235JRH	6	216	0,77	4,62	0,19	

Logo 1	Logo 2	2/2
Site address		
<b>PART LIST</b>		
Document number:		Phase

Position	Profile	Material	Qty:	Length [mm]	Weight [kg]	Tot. weight [kg]	P. Area [m2]	Remarks
P-20203	CHS48.3*3.2	S235JRH	6	1108	3,94	23,64	1,00	
P-20204	CHS48.3*3.2	S235JRH	2	1113	3,96	7,92	0,33	
P-20205	CHS48.3*3.2	S235JRH	2	1119	3,98	7,96	0,34	
P-20208	CHS48.3*3.2	S235JRH	2	71	0,26	0,51	0,02	
P-20209	CHS48.3*3.2	S235JRH	2	1071	3,81	7,62	0,32	
P-20210	CHS48.3*3.2	S235JRH	1	863	3,07	3,07	0,13	
P-20211	CHS48.3*3.2	S235JRH	1	1175	4,18	4,18	0,18	
P-20212	CHS48.3*3.2	S235JRH	1	2160	7,68	7,68	0,32	
P-20213	CHS48.3*3.2	S235JRH	1	1960	6,97	6,97	0,29	
P-20216	CHS48.3*3.2	S235JRH	2	766	2,73	5,45	0,23	
P-20217	CHS48.3*3.2	S235JRH	1	859	3,06	3,06	0,13	
P-20218	CHS48.3*3.2	S235JRH	1	3814	13,56	13,56	0,57	
P-20219	CHS48.3*3.2	S235JRH	1	2400	8,54	8,54	0,36	
<b>P-20220</b>	CHS48.3*3.2	S235JRH	3	3985	14,17	42,52	1,79	
<b>P-20221</b>	CHS48.3*3.2	S235JRH	1	4838	17,21	17,21	0,73	
P-20222	CHS48.3*3.2	S235JRH	1	3819	13,58	13,58	0,57	
P-20223	CHS48.3*3.2	S235JRH	1	2018	7,18	7,18	0,30	
<b>P-20224</b>	CHS48.3*3.2	S235JRH	1	<b>1067</b>	<b>3,80</b>	<b>3,80</b>	<b>0,16</b>	
P-20225	CHS48.3*3.2	S235JRH	4	1461	5,20	20,79	0,88	
P-20226	CHS48.3*3.2	S235JRH	6	1231	4,38	26,28	1,11	
P-20227	CHS48.3*3.2	S235JRH	1	2425	8,63	8,63	0,36	
<b>P-20229</b>	CHS48.3*3.2	S235JRH	1	4834	17,19	17,19	0,73	
<b>P-20230</b>	CHS48.3*3.2	S235JRH	1	1764	6,27	6,27	0,26	

Sum:

133

1770 kg

53 m2

**Deleted positions:**

P-2102	BL6*160	S235JR	2	784	5,9158	11,8315	0,525
P-2104	BL6*160	S235JR	4	787	5,8754	5,87544	0,261
P-20214	CHS48.3*3.2	S235JRH	4	1178	4,1903	4,19026	0,177
P-20215	CHS48.3*3.2	S235JRH	4	841	2,9929	2,99292	0,126